

softMC Training – Module 7

Motion



Topics

- Motion Elements
- Single Axis
- Groups
- Enabling Motion
- Element Properties
- System Properties
- Modal/Nodal Properties
- Motion Types
- Motion Commands
- Motion Blending

MOTION ELEMENTS

Motion Elements (also called Elements)

- Motion element is any object on which a motion command can be executed
- Motion element refers to both axes and groups.
- Axis – a single motion axis (drive + motor and associated properties)
- Group – a collection of axes
- Motion elements are defined in Config.prg or Terminal

Element Properties

- Properties are used primarily for defining the characteristics of the motion
- Axis Properties
- Group Properties
- Many property names (and commands) are used for both axes and groups.

Element Properties

- Syntax

`<element>.<property> = <value>`

- Examples (Properties)

`Axis.Acceleration = 100`

`Joint.Jerk = 1000`

`Robot.Deceleration = 500`

Element Properties

- Example – Axis Motion

```
A1.Acceleration = 100
```

```
A1.VelocityCruise = 1000
```

```
A1.Deceleration = 50
```

```
Move A1 1567
```

```
    '1567 is the target position
```

- Example – Group Motion

```
MyGroup.Acceleration = 100
```

```
MyGroup.VelocityCruise = 1000
```

```
MyGroup.Deceleration = 50
```

```
Move MyGroup {10,20,35,50}
```


```
    'target positions of each axis
```

```
    'in the group
```

SINGLE AXIS

What is an Axis?

- What is an axis?
 - Motor
 - Drive
 - Components of softMC



Defining Axes

- System default axis names: A1, A2, A3 ...
- Recommended to give axes meaningful names , using `<axis>.AxisName` property
- Axes are defined/renamed in config.prg
- Must be the first command, before Program
- Syntax

```
Sys.Naxes = <number>
```

```
...
```

```
Program
```

```
...
```

```
End Program
```

- Example

```
Sys.Naxes = 2
```

```
...
```

```
Program
```

```
A1.AxisName = Xaxis
```

```
A2.AxisName = Lift
```

```
...
```

```
End Program
```

Axis Setup Procedure

- Axis setup procedure detailed in wiki:
http://softmc.servotronix.com/wiki/Axis_Setup_Procedure

Properties - Axis Setup Subroutine

```
sub SetRotAxis(ax as generic axis, byval minval
  as double , byval maxval as double)
with ax
  attach
    En = 0
    AxisType = 1
    PositionFactor = pos_unit/360
    VelocityFactor = PositionFactor /1000
    AccelerationFactor = VelocityFactor /1000
    Jerkfactor = AccelerationFactor /1000
    VelocityMax = 1000
    AccelerationMax = 10000
    DecelerationMax= 10000
    JerkMax = 20*amax
    VelocityCruise = 0.5*VelocityMax
    Acceleration = AccelerationMax
    Deceleration = DecelerationMax

    Jerk = JerkMax
    PrfType = -1
    Smooth = -1
    VelocityOverspeed = 1.2*VelocityMax
    VelocitySafetyLimit = 10*VelocityMax
    PositionErrorDelay = 2
    PositionErrorMax = 1
    PositionMax = maxval
    PositionMin = minval
    PositionMaxEn = 1
    PositionMinEn = 1
    PositionRolloverEnable = 0
  detach
end with
end sub
```

GROUPS

What Is A Group?

- A group is a combination of axes that are setup to work together.
 - XYTable (A1, A2)
 - Robot (A1, A2, A3)
- Groups enable control of multiple axes as a single mechanism.
- No limit to number of axes in a group.
- All axes in the system may be part of one group.
- One axis can belong to several groups but only one group can be active (attached) at a time.

Create a Group

- A group can be defined only in Config.prg or Terminal
- To set up a Group, first set up each of the axes that will be in the group.
- Then, form the group by using the command **Common Shared ... as Group**

- Syntax

```
Common Shared <group> as Group AxisName = <axis> {AxisName = <Axis>}
```

- Example

```
Common Shared MyGroup as Group AxisName = A1 AxisName = A2
```

Group Properties

- Once a group is defined, group properties can be set
- Properties of a group are set like properties of a single axis

Properties – Group Setup Subroutine

```
sub SetGroup(gr as generic group)
  dim i as long
  with gr
    attach
      en = 0
      sleep 10
      vfac = 1/1000
      afac = vfac/1000
      jfac = afac/1000
      positionerrorsettle = 2
      pemax = 1
      abs = 1

      a1.axistype = 0
      a2.axistype = 0
      a3.axistype = 0

      configgroup

      vmax = 1000 ' mm/sec
      amax = 1500 ' 1500 mm/sec^2
      dmax = 1500 ' 1500 mm/sec^2
      jmax = omega*amax
      vcruise = vmax
      acc = amax
      dec = dmax
      jerk = jmax

      vmtran = vmax
      amtran = amax
      jmtran = jmax
      vtran = vmtran
      atran = amtran
      dtran = amtran
      jtran = jmtran

      vmrot = vmax
      amrot = amax
      jmrot = jmax
      vrot = vmrot
      arot = amrot
      drot = amrot
      jrot = jmrot

      xmax = 300
      xmin = 0

      ymax = 300
      ymin = 0

      zmax = 300
      zmin = 0

      rmin = 0
      rmax = 4000

      smooth = -1
      prftype = profile

      j1.pmin = 0
      a1.pmin = 0

      j2.pmin = 0
      a2.pmin = 0

      j3.pmin = 0
      a3.pmin = 0

      j1.pmax = 300
      a1.pmax = 300

      j2.pmax = 300
      a2.pmax = 300

      j3.pmax = 300
      a3.pmax = 300

      Print "group ";elementname;" set."
      detach
    end with
  end sub
```

ENABLING MOTION

Prerequisites for Motion – Attach

- Attaching prevents other tasks from attempting to control the axis
- An axis can only be attached to one task at a time
- To **attach** the axis to the controlling task

`Program`

`Attach <axis>`

- To **detach** the axis:

`Detach <axis>`

- All axes are automatically detached at the end of a task
 - If Detach is issued while profile motion for the axis is in progress, Detach is not executed until that motion is complete
- Motion commands from the Terminal implicitly attach/detach motion elements
 - For example, Move command from Terminal implicitly attaches the element before the move and implicitly detaches it after the command has executed.
- Stop/Proceed mechanism temporarily takes control of the motion element

Prerequisites for Enabling Motion

- Physical drive
 - Drive enabled
- System
 - System enabled
 - System logical motion flag On
- Motion element
 - Element enabled
 - Element logical motion flag On

Prerequisites for Enabling Motion – Drive

- Remote enable must be configured
 - INMODE set to define use of remote enable
 - Remote Enable signal is not a prerequisite for a motion bus system
- Software enable (signal from motion bus)
 - No faults
 - Software Enable = EtherCAT controlword
- STO – Safe Torque Off
 - An electrical signal to the drive. If removed, drive cannot be enabled.

Prerequisites for Enabling Motion – System

- System enabled
 - **System.Enable = 0** immediately disables all motion elements
 - **System.Enable = 1** allows all motion elements to be explicitly enabled

- Motion flags must be turned on
 - **System.Motion = 0** inhibits motion
 - **System.Motion = 1** allows motion

- Motion flag is cleared (set to 0) when an unhandled error occurs
- Motion flag can be set only from Terminal

Prerequisites for Enabling Motion – Element


- Element enabled
 - **<element>.Enable = 0** immediately disables the motion element
 - **<element>.Enable = 1** enables the motion element
- If *<element>* is a group, enabling the group enables all axes in the group
- Motion flags must be turned on
 - **<element>. Motion = 0** inhibits motion
 - **<element>. Motion = 1** allows motion
- Element motion flags are not affected by the error handler

3 Phases of Motion Generation


- Task issues an instruction for the movement.
- Motion manager task prepares the motion for execution.
- At every sample the next point of the path/trajectory is computed, and sent via motion bus to the drive.

- Example

`Move A1 1000 VelocityCruise = 10`



End of Motion



MOTION ELEMENT PROPERTIES by Category

- Applicable to all Motion Elements

Properties – Profile

Long Form

- *<element>*.Acceleration
- *<element>*.AccelerationMax
- *<element>*.AccelerationRate

- *<element>*.Deceleration
- *<element>*.DecelerationMax
- *<element>*.DecelerationRate

- *<element>*.SmoothFactor

- *<element>*.VelocityCruise
- *<element>*.VelocityMax

Short Form

- *<element>*.ACC
- *<element>*.AMAX
- *<element>*.ARATE

- *<element>*.DEC
- *<element>*.DMAX
- *<element>*.DRATE

- *<element>*.SMOOTH

- *<element>*.VCRUISE
- *<element>*.VMAX

Properties – Jerk

- Jerk can be active only if `<element>.smooth = -1`

Long Form

- `<element>.Jerk`
- `<element>.JerkMax`
- `<element>.JerkRate`

Short Form

- `<element>.JERK*`
- `<element>.JMAX`
- `<element>.JRATE`

- **same as long form*

Properties – Velocity Vector

Long Form

- `<element>.VelocityCommand`
- `<element>.VelocityFeedback`

Short Form

- `<element>.VCMD`
- `<element>.VFB`


Properties – Velocity Scalar

Long Form

- `<element>.VelocityCruise`
- `<element>.VelocityFinal`
- `<element>.VelocityMax`
- `<element>.VelocityOverride`
- `<element>.VelocityRate`
- `<element>.VelocityOverSpeed`

Short Form

- `<element>.VCRUISE`
- `<element>.VFINAL`
- `<element>.VMAX`
- `<element>.VORD`
- `<element>.VRATE`
- `<element>.VOSPD`



Properties – Units

Long Form

- *<element>*.VelocityFactor
- *<element>*.AccelerationFactor
- *<element>*.JerkFactor

Short Form

- *<element>*.VFAC
- *<element>*.AFAC
- *<element>*.JFAC

Properties – Position Vector

Long Form

- *<element>*.PositionCommand
- *<element>*.PositionFeedback
- *<element>*.PositionToGo

Short Form and Examples

- *<group>*.PCMD
Move MyGroup {5.5,6.5}
- *<group>*.PFB
?MyGroup.PFB
{5.5,6.5}
- *<group>*.PTOGO
?MyGroup.PTOGO
{1.324,2.324}

Properties – Position Scalar

Long Form

- *<element>*.PositionError
- *<element>*.PositionErrorSettle
- *<element>*.TimeSettle
- *<element>*.TimeSettleMax
- *<element>*.Absolute

Short Form

- *<element>*.PE
- *<element>*.PESETTLE
- *<element>*.TSETTLE
- *<element>*.TSETTLEMAX
- *<element>*.ABS

MORE MOTION ELEMENT PROPERTIES

- Applicable to all Motion Elements

Properties – Motion Attributes

- **Absolute (Abs)** – specifies whether movement is absolute or incremental

```
<element>.absolute  
    'absolute motion
```

```
<element>.absolute = 0                                'relative motion
```

- Syntax

```
<element>.ProfileType
```

- Examples

```
<element>.ProfileType = -1                                'sine acceleration;  
    S-curve
```

```
<element>.ProfileType = 1                                'trapezoidal  
    velocity
```

```
<element>.ProfileType = 2                                'trapezoidal  
    acceleration; S-curve
```

Properties – Motion Monitoring

- `<element>.isMoving (0,1,2,3)`
- `<element>.isSettled (0,1)`
- `<element>.iType`

Properties – StartType

- **StartType** defines the condition under which an **element** starts a move
 - Immediate (1) – after 5 samples (5 communication bus cycles)
 - InPosition (2) – previous motion has settled
 - GeneratorCompleted (3) – previous motion profile has completed
 - SyncStart (4) – used with SYNC command, to synchronize multiple motion elements
 - SuperImmediate (5) – immediately

- Syntax

`<element>.StartType`


- Example

`MyGroup.StartType = Immediate`

`MyGroup.StartType = 1`

Properties – StartType Illustration

- Movement of A to B is interrupted by Move C command according to StartType value:
 - Immediate (1)
 - InPosition (2)
 - GeneratorCompleted (3)
 - SuperImmediate (5)



Properties – StopType

- **StopType** defines how an **element** responds to the **Stop** command
 - Immediate (1)
 - OnPath (2)
 - EndMotion (3)

- Syntax

`<element>.StopType`

- Example

`MyGroup.StopType = OnPath`

`MyGroup.StopType = 2`

Properties – ProceedType

- **ProceedType** defines how an **element** responds to the **Proceed** command
 - Continue (1)
 - NextMotion (2)
 - ClearMotion (3)

- Syntax

`<element>.ProceedType`

- Example

`MyGroup.ProceedType = Continue`

`MyGroup.ProceedType = 1`

SYSTEM PROPERTIES

System Properties that Affect Motion

- Sys.Vord
- Sys.Motion
- Sys.En
- Sys.vRate, Sys.dRate, Sys.aRate, Sys.jRate *

* Note that the term “**Rate**” in this context **indicates a limiting value**, and not a rate of change,

MODAL and NODAL SETTINGS

Modal vs. Nodal Settings

- **Modal Setting** – a fixed value
 - Assigned explicitly in a program line:
`MyAxis.Acceleration = 100`
 - Value persists until the property is assigned a different value
 - Value is used for motion commands unless specified otherwise by a nodal setting
- **Nodal Setting** – a temporary value, used for one motion command only
 - Overrides the modal setting
 - Included in the motion command

- **Example**

```
MyAxis.Acceleration = 100  
    'modal setting (100)
```

```
Jog MyAxis 5000 Acceleration = 10    'nodal override (10)
```

Modal vs. Nodal Settings

- Modal setting (MyGroup is a group comprised of 4 axes)

...

```
MyGroup.Acceleration=1000
```

...

```
Move MyGroup{10,10,-10,0}
```

...

- Nodal setting

```
Move MyGroup{10,10,-10,0} Acceleration = 500
```

...

MOTION TYPES AND COMMANDS

Motion Types – Interpolation

- **Move** – joint (natural) interpolation
- **MoveS** – straight, world-space interpolation
- **Circle** – circular (arc) interpolation
- **Jog** – unlimited axis movement at constant speed
- **Delay** – movement delay
- **SyncStart** – synchronized start of several elements

Move – Joint Interpolation

- Joint interpolated move
- Velocity determined by the “slowest” axis
- VCRUISE, ACC, DEC

Circle – Circular Motion

- Circular motion defined by angle, center and plane
 - helical motion - possible
- Circular motion defined by start, target and arc-point

Jog

- Axis only
- Pure velocity move
- Time can be limited or endless
- Used for conveyer motors and similar applications

SyncStart

- Two or more motion elements begin to move at the same time (synchronized movement)
- Syntax

```
SyncStart a1, g2, scar1
```

Delay

- DELAY – delays the motion sequence but not the program sequence (“dwell”)
- SLEEP – delays program execution, but not motion

- Syntax

`DELAY <element> <time in ms>`

MOTION BLENDING

Motion Blending

- A process in which motion is not stopped between motion commands
- 4 types of blending:
 - Concatenation - specifies a non-zero value for V_{final} (velocity at end of motion)
 - Continuous path (CP) – two motions are combined in a controlled manner
 - Superposition (SP) – two motions are superimposed on each other
 - Advanced interpolation (AI) – blending performed on entire array of points
- http://softmc.servotronix.com/wiki/Motion_Blending

END